



## 110.2" (2.8m) Laminated Frontlit

Item Code: BS-LF011-110R-GL-G



FOB Price: **\$159/roll**

Mini Order: 40 rolls


Average Rating: 1b (kg)

[Inquire Now](#)

### Overview

#### Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.



**Product Description:**

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

**Packing:**

Inner cores are packed with craft paper or hard tube.

**Application:**

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

---

## Specifications

---

Item	Metric	Test Method
Weight	440±10 gsm	DIN53352 BS3424
Breaking Strength	1350/1200 N/2.0" (5cm)	DIN53354 BS3424
Tearing Strength	245/185 N	DIN53356 BS3424
Adhesion	60 N/2.0" (5cm)	DIN53357 BS3424
Width	Up to 11.5' (350cm) (1010)	
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701	
Lacquering	Products can be lacquered with ACRYLIC or PVDF	
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3	



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com