



125.9" (3.2m) Coated Frontlit

Item Code: BS-CF013-1-125R-GL



FOB Price: **\$291/roll**

Mini Order: 40 rolls

Average Rating: lb (kg)

[Inquire Now](#)

Overview

Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.

Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.



Specifications

Item	Metric	
Weight	440±10	gsm
Breaking Strength	1800/1300	N/2.0" (5cm)
Tearing Strength	180/165	N
Adhesion	80	N/2.0" (5cm)
Width	Up to 11.5' (350cm) (0505)	
FR Certification	We can reach:M2,B1,B2,DIN75200,NFPA701	
Lacquering	Products can be lacquered with ACRYLIC or PVDF	
Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se%	We can reach:EN71-3	



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com