



3.2M LA series Solvent Printer(XAAR382-35PL)

Item Code: LFIP-MJT-LA3208XR382



FOB Price: **\$15,712/set**

Mini Order: 1 set

Shipping Weight: ★★☆☆☆

Average Rating: 2886.4lb (1312kg)

[Inquire Now](#)

Overview

Description:

- . Xaar proton printhead.
- . Separate ink pressure system, saving ink and decreasing the cost for the clients.
- . Removable leg, decreasing the freight of the clients.
- . Photoelectricity sensor and automatic correction system.
- . Three-heating system: Pre-heater, printer heater, and after heater, adjust the suitable temperature of the media, increasing the printing quality.
- . Use the ink which is certified by Xaar, increase the speed 70% base on the original speed.

PACKING SIZE: 187.4"*37.4"*53.1" (4760*950*1350mm)

Net Weight/Gross Weight: 1433.0lb (650kg)/1653.5lb (750kg)

Details:



Details

| | |
|--------------------|-------------------------------------|
| Colors | C,M,Y,K |
| Print Speed | 90?/h 2pass |
| Maximum Resolution | 720dpi |
| Max Media Width | 126.0" (3200mm) |
| Ink type | Solvent Inks |
| Print head | XAAR PROTON Printhead?8 printheads? |
| Max print width | 126.0" (3200mm) |

Specifications

| Model | | LA3208XR382 |
|---------------------|---|-------------|
| Printing Type | Separation Printing | |
| Printing Technology | Piezo printing | |
| Printhead Type | XAAR PROTON Printhead(8 printheads) | |
| Media Transmission | Roll-to-roll | |
| Printing Port | High speed USB boards | |
| Data Transmission | Fabric Cable | |
| Output Model | Rip Printing/Printing After RIP/Net-print | |
| RIP Software | Photoprint,Ultraprint | |
| Printing Mode | 4 Colors with 8 printheads | |
| Speed | High speed: | 90?/h 2pass |
| | Mid speed: | 75?/h 3pass |
| | Low speed: | 60?/h 4pass |
| Heating System | Four heaters: front heater, bed heater, rear heater and printhead heater | |
| Cleaning System | Air pressure and suction cleaning | |
| Frame Structure | Steady steel structure is used on the machine body, and the combination of aluminum and steel on the girder | |
| Color | C,M,Y,K | |

| | |
|-----------------------|--|
| Power Requirement | 220V AC |
| System | 220V±10%,<4A,50/60HZ |
| Heating | 220V±10%,<16A,50/60HZ |
| Operation Environment | Temperature:20°C?25°C ;Humidity:40%?70%RH |
| Printing Resolution | Adjustable(From 240dpi,360dpi to 1440dpi) |
| Media Types | Banner, adhesive vinyl, PVC self adhesive, backlit, Flex media within 0.2" (5mm) thickness |
| Printing/Media Width | 71.0" (1800mm), 98.4" (2500mm),126.0" (3200mm) |



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com