



## 43" Cabinet Frame Full-auto Double Sides Hot Laminator

Item Code: FMJ-1100-RFZS



FOB Price: **\$4,294/set**

Price: **\$4,000/set**

You Save: **\$294.00(7%)**

Mini Order: 1 set

Shipping Weight: ★★★★★

Average Rating: 704.0lb (320kg)

[Inquire Now](#)

### Overview

#### Cabinet Frame Full-auto Self-peeling and Dual Rollers Heated Model.

Designed for both Board and Rolling Medium.

Roll-to-roll supported operation to maximize productivity

Laminating procedures: Single and double sides hot laminating;, single and double sides cold laminating

The FMJ-RFZS series laminator is capable of running a wider range of media and can generate higher process speeds, which make this range of machines ideal for business that are looking to build in extra capacity and more versatility.

It's a perfect fit for owners of lower-end laminators, looking to upgrade into `a` professional production machine.

The machine is available in 43.3" (1100mm), 51.2" (1300mm), 63.0" (1600mm), 66.9" (1700mm), 80.7" (2050mm), and 90.6" (2300mm)model

#### Products highlights:

- . Dual heat rollers and temperature controllers' that allows to control the temperature respectively.
- . 43" (1,092mm), 51" (1,295mm), 63" (1,600mm), 67" (1,702mm), 81" (2,057mm), and 91"(2,311mm) working film width for your convenience.
- . 3" (76mm) core auto-grip rollers for easy laminating film setup.
- . 5" (127mm) rollers for best quality laminating control. 1" (25mm) maximum nip opening for wide range substrates.
- . Easy operation panel:
  - Forwardand backward control
  - Foot pedal control
  - Various speed and temperature adjustment
  - Emergency stop button
- . In order to coat different media thickness, the laminator is equipped with a roller that comes with a lifting height indicator.
- . Paired with photocell eye, it can protect the roller from damaged.
- . Offer industrial performance at exceptional value.
- . Good choice for high-end volume user for mounting, laminating and encapsulating projects.
- . Roll-to-roll supported operation to maximize productivity
- . Electric model, with stepless speed regulating, foot pedal switch for hands free operation.
- . Automatic take-up roll for both printed images and back paper.
- . The cabinet frame design makes the structure more stable for working.

- . Silicone high release rollers for easy cleaning.
- . The laminator is equipped with optical sensor and emergency stops for a safety operation.

**Application:**

After printing finishing equipment. Available for photographic, advertising and copy shops to do lamination work, adding protective layer on books cover, photography, color pages, documents, charts, drawings, indoor advertising products, etc.

**Applicable laminating medium:**

Photopaper, PP, part of self adhesive PP, backlit film or transparent film.

**Warranty and aftersales service:**

One year warranty.  
 24-hour technical support services by email or calling.  
 User-friendly English manual for machine using and maintenance.

**Details**

Maximum Laminating Width	43" (1100mm)
Maximum Laminating Thickness	1" (25mm)
Rollers Diameter	5" (128mm)
Maximum Laminating Speed	197" (5m) / min
Maximum Internal Diameter of	3"
Profile	Full-auto hot / cold laminator machine (Automatic take-up roll for both printed images and back paper by one

**Specifications**

**Specification:**

hot laminating, single sided or double sides cold laminating, low temperature cold laminating, mounting and encapsulating. Cabinet Frame, all-metal casing shell, more stable working performance. Dual heat rollers and temperature controllers, which can control temperature respectively. High value-added products- Capable of running a wider range of media and can generate higher process speeds.

Model	FMJ-1100-REZS	
Max. laminating width	43.3" (1100mm)	rollers and temperature controllers, which can control temperature respectively. High value-added products- Capable of running a wider range of media and can generate higher process speeds.
Max. laminating thickness	0.9" (23mm)	Top and bottom
Heated roller		generate higher process speeds.
Max. heating temperature		150°C
Roller heating temperature		40-50°C
Upper roller during cold laminating		40-50°C
General setting during hot laminating		100°C
Laminating speed		0-196.9" (0-5m)/min

Forward / Reverse	Yes
Foot pedal	Yes
Emergency stop	Yes
Auto rewind liner pickup	Yes
After laminating pickup	Yes
Roller's diameter	5.1" (130mm)
Media core size	3"
Heating power	2000W / single roller heating, 5000W / double rollers heating
Motor power	90W
Power	The voltage is up to the local requirement, like AC 80V-110V, AC 110V-240V, AC 380V; The current is 50 / 60Hz
Machine weight	529.1lb (240kg)
Machine dimension	58.3" x 24.0"* x 50.4" (1480 x 610 x 1280mm)
Package	Fumigation free package
Packing size	61.4" x 27.6" x 55.1" (1560 x 700 x 1400mm)
Gross weight	320kg (705.5lb)

## Tags

[43" Cabinet Frame Full-auto Double Sides Hot Laminator](#) [43" Double Sides Hot Laminator](#)



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com