



63" Low Temp Cold Laminator

Item Code: FMJ-1600-RFX



FOB Price: **\$2,652/set**

Price: **\$2,350/set**

You Save: **\$302.00(11%)**

Mini Order: 1 set

Shipping Weight: ★★★★★

Average Rating: 440.0lb (200kg)

[Inquire Now](#)

Overview

Application: After printing equipment. Available for Ad. Shop, photography, and copy shop to do lamination work, adding a protective layer on books cover, photography, color pages, documents, charts, drawings, indoor advertising products, etc.

Applicable Laminating Medium: Photo paper, self adhesive PP, backlit film or transparent film.

Product Highlights:

FMJ-1600-RFX cold laminator adopts low temperature cold laminating technology-mainly used to solve the issue that cold laminated images are hazy.

Driven by electric, includes floor stand and foot pedal switch

Electric model, stepless speed regulating.

It comes with foot pedal with forward and reverse control to free your both hands to handle the work being processed.

High release silicone rollers - for easy cleaning.

Note: If you want to use cold laminating film for single laminating or mounting (thickness less than **0.2"**), and your max. Laminating width is **63.0" (1600mm)**, this low temp cold laminator is your best choice.

Operating Method: Electric

Max. Laminator Width: 63.0" (1600mm)

Roller's Diameter: 4.0" (102mm)

Max. Laminating Thickness: 0.2" (5.5mm)

Max. Heating Temperature: 60 degree

Laminating Speed: From 0` to 157.5" (4000mm) per minute

Foot Pedal: Yes

Forward/Reverse: Yes

Machine Color: Red or black

Lifting Mode for Rollers: Manual Lifting on one side

Heating Power: 2.5KW (Single roller)

Motor Power: 90W

Power Supply: The voltage is up to the local requirement, like AC 80V-110V, AC 110V-240V, the frequency is 50Hz or 60Hz.

Details

Maximum Laminating Width	63" (1600mm)
Maximum Laminating Thickness	0.4" (10mm)
Rollers Diameter	4" (102mm)
Maximum Laminating Speed	197" (5m) / min
Maximum Internal Diameter of	3"
Profile	Adopts low temperature cold laminating, mainly used

to solve the issue that cold laminated images are

Specifications

hazy. Stand frame construction, automatic take-up

rolls of back paper.

Specification Form	
Operating Method	Electric
Max. Laminator Width	63.0" (1600mm)
Roller's Diameter	4.0" (102mm)
Max. Laminating Thickness	0.2" (5.5mm)
Max. Heating Temperature	60 degree
Laminating Speed	From `0` to 157.5" (4000mm) per minute
Foot Pedal	Yes
Forward/Reverse	Yes
Machine Color	Red or black
Lifting Mode for Rollers	Manual Lifting on one side
Heating Power	2.5KW (Single roller)
Motor Power	90W
Power Supply	The voltage is up to the local requirement, like AC 80V-110V, AC 110V-240V, the frequency is 50Hz or 60Hz.

Tags

[63" Low Temp Cold Laminator Machine](#) [Cold Laminator Machine](#)

QA

Q	can you advise whether it is the one of the rollers that heats up? - or whether the heating is achieved by an infrared strip and a blower fan?
A	For this series machine ,there has only top roller with infrared heating lamp?without cooling fan . Reply by sign-in-china
Q	Can this model laminate thicker than 5mm ?
A	yes .the Max laminate thickness is 10mm . Reply by sign-in-china
Q	Can i use on Roland SP-540V ?
A	yes ?you can use this encoder strip to Roland SP-540V. Reply by sign-in-china



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com