



98.4" (2.5m) Laminated Frontlit

Item Code: BS-LF010-98R-GL-W/G



FOB Price: **\$122/roll**

Mini Order: 40 rolls


Average Rating: lb (kg)

[Inquire Now](#)

Overview

Product Characteristic:

- . Completely light tight.
- . Anti-UV, weather-resistant.
- . Mildewproof, antifouling processed surface.
- . Could be printed directly or with the film.
- . Strong structure, anti-typhoon.
- . Flame retardant, safe.
- . Bearing chemistry solvent.



Product Description:

Good smoothness, high bonding strength, stable ink absorbing, expressive force, self-cleaning, faster drying, perfect printing ability, anti-UV surface.

Packing:

Inner cores are packed with craft paper or hard tube.

Application:

Signage, digital printing, screen printing for banner and outdoor, indoor digital printing and so on.

Specifications

| Item | Metric | Test Method |
|-----------------------------|--|-----------------|
| Weight | 440±10 gsm | DIN53352 BS3424 |
| Breaking Strength | 850/750 N/2.0" (5cm) | DIN53354 BS3424 |
| Tearing Strength | 185/135 N | DIN53356 BS3424 |
| Adhesion | 60 N/2.0" (5cm) | DIN53357 BS3424 |
| Width | Up to 11.5' (350cm) (0505) | |
| FR Certification | We can reach:M2,B1,B2,DIN75200,NFPA701 | |
| Lacquering | Products can be lacquered with ACRYLIC or PVDF | |
| Cd%,Pb%,As%,Ba%,Cr%,Hg%,Se% | We can reach:EN71-3 | |



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com