



[Blue Color Flexible LED Strip\(30 SMD 5050 leds per meter waterproof IP65\)](#)

Item Code: LED Strip-CM-5050B12V30WF65



Mini Order: 1 roll

Average Rating: 1b (kg)

[Inquire Now](#)

Overview

Weatherproof flexible LED light strip with 3-chip 5050SMD LEDs.IP Rating:IP65 .Available in 5 meter (197 in), 1 meter (39 in) and 1/2 meter (19.5 in) lengths. Weatherproof flexible light strips with adhesive backing, can be cut into 3-LED segments. 12VDC operation.

Product Feature:

1. 5 meter (197 in)/Roll
2. 5050 SMD LED as light source,super luminous flux,large viewing angle,even lighting,low attenuation.
3. Best cost performance,high color consisence.
4. Energy saving,environment-friendly,long life span 50,000hrs.


Application:

Widely used for architectural decorative lighting, amusement park, theater and aircraft cabin mood lighting, hallway and walkway lighting, stairway accent lighting, art lighting for signage letters, cove lighting, emergency exit path lighting, cabinet and under counter lighting, exhibition stands and panels, display cases, etc.

Product Photos:




Three Space Dimensions:



Application:



Connection Diagram (mm):




Notes:

1. The thickness of the wires shall be adopted based on the possible current products power, length of the wire extension(5meter at maximum as recommended) and the loss in the wires transit at low voltage.
2. The both ends of extension shall be sealed with as waterproof.
3. Don't work under the situations of touching in static-electronics environments or light on.
4. The strip can be connected to 5m at maximum and no exceed.
5. Suggest choosing high-qualified switch power(have shortelectronics ,overvoltage and overloading protection function etc).
6. Acid silicone glue is forbidden.

Packing:



5m/bag. 0.14kg/bag
 15bags/inner box 3.1kg
 30bags/outer box
 150m/outer box 6.7kg/outer box



5m/bag. 0.14kg/bag
 15bags/inner box 3.1kg
 30bags/outer box
 150m/outer box 6.7kg/outer box



1. Bigger carton:45x25x25.6cm ; Small carton:23x21.6x22.6cm ; Aluminium-Foil bag:220x240x0.12mm.
2. 150pcs LEDs per/5m,5m per reel,one reel in one aluminum -foil bag.
3. 15 bags in one small carton . (75m in one small carton).
4. One bigger carton contains two small cartons . (150m in one bigger carton).
5. N.W: 4.9± 10?Kg/bigger carton.
6. G.W: 6.7± 15?Kg/bigger carton.

Specifications

| Angle(°) | Color | Luminous(lm) | Wavelength Scope (nm/K) | Working Voltage(V) | Power(W) | Life S | |
|----------|--|--------------|-------------------------|--------------------|-------------------------------|---------------|--------|
| ?120 | Red | 60-108lm | 620-630nm | DC12V | 36W | 50 | |
| ?120 | Green | 228-270lm | 520-530nm | DC12V | 36W | 50 | |
| ?120 | Blue | 54-72lm | 465-475nm | DC12V | 36W | 50 | |
| ?120 | Yellow | 66-90lm | 588-595nm | DC12V | 36W | 50 | |
| ?120 | White | 330-420lm | 5500-6500K | DC12V | 36W | 50 | |
| ?120 | Warm White | 330-420lm | 2800-3200K | DC12V | 36W | 50 | |
| ?120 | Cool White | 330-420lm | 8000-10000K | DC12V | 36W | 50 | |
| Others | | | | | | | |
| LED No. | Cascade QTY | IP degree | FPC width/color | Driving Type | Installation | Working temp. | Stor |
| 150pcs | 5m | IP65 | 10mm/white | constant voltage | 20mm,3M double-sided adhesive | -40? —+50? | -40? - |
| Wires | length150mm,20AWG line Red&Black wires, Red=positive wire, Black=negative wire | | | | | | |

Tags

[Flexible LED Strip\(30 SMD 5050 leds per meter waterproof IP65\)](#)



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com