



## P7.62 Indoor single Color LED message board

Item Code: SCMB-LJ-P7.62Indoor



FOB Price: **\$475/sq.m**

Mini Order: 1 roll

Average Rating: lb (kg)

[Inquire Now](#)

### Overview



The Single Color LED Screen is widely used for indoor display messaging. It is featured

with a wide range angle and distance view, uniform illumination and excellent brightness. There is a low rate of failures; the LED screen has a long lifespan, low consumption of energy and excellent performance.

#### Application:

The Single Color LED Screen is design to function as an indoor scrolling message display; it can also work in a network system with other displays. It can be used in banks, hospitals, mall, hotels and much more.

### Specifications

#### Specification:

Pixel pitch	0.3" (7.62mm)
-------------	---------------

Pixel configuration	1R
Pixel Density	17222dots/?
Ideal viewing distance	29.5'-85.3' (9m-26m)
Ideal viewing angle	140°
Control method	Synchronization/ Asynchronization
Driving method	Constant 1/16 scanning
Frame frequency	?60HZ
Refresh frequency	?180HZ
Max. power	<300W?
Brightness	?200cd/?
IP grade	IP20 front
Voltage range	?AC220v/110±10%
Ideal temperature	-10??+45?
MTBF	More than 10,000 hours
Lifespan	10,000 hours



Copyright © 1999-2012 by Beijing ChinaSigns Information Company Limited All Rights Reserved.

Email:info@sign-in-china.com Tel:+86 132 6410 3286 www.sign-in-china.com